

JUHONG PACKING MATERIAL				Terra (砥石系列)			Ridge (擎岭系列)			Pivot (星枢系列)			Duro (峰极系列)			Nexa (穹界系列)					
Width		Thickness		Average Strength			Average Strength			Average Strength			Average Strength			Average Strength			Length/Weight		Coil
in	mm	in	mm	lbs	N	N/mm ²	lbs	N	N/mm ²	lbs	N	N/mm ²	lbs	N	N/mm ²	lbs	N	N/mm ²	ft/lb	m/kg	Winding
1/2	12.7	0.015	0.38	706	3137	650	/	/	/	/	/	/	/	/	/	/	/	/	39.2	26.5	M/R
1/2	12.7	0.020	0.51	947	4210	650	1093	4858	750	1209	5376	830	1282	5700	880	1428	6347	980	29.4	19.8	M/R/O/J
1/2	12.7	0.023	0.58	1077	4788	650	1243	5525	750	1375	6114	830	1458	6482	880	1624	7219	980	25.6	17.2	M/R/O/J
5/8	16	0.015	0.38	889	3952	650	/	/	/	/	/	/	/	/	/	/	/	/	29.6	20.0	M/R
5/8	16	0.020	0.51	1193	5304	650	1377	6120	750	1524	6773	830	1615	7181	880	1799	7997	980	23.6	15.9	M/R/O/J
5/8	16	0.023	0.58	1357	6032	650	1566	6960	750	1733	7702	830	1837	8166	880	2046	9094	980	20.5	13.8	M/R/O/J
3/4	19	0.020	0.51	1417	6299	650	1635	7268	750	1809	8043	830	1918	8527	880	2136	9496	980	19.6	13.2	M/R/O/J
3/4	19	0.023	0.58	1611	7163	650	1859	8265	750	2058	9147	830	2182	9698	880	2429	10800	980	17.1	11.5	M/R/O/J
3/4	19	0.028	0.71	1973	8769	650	2276	10118	750	2519	11197	830	2671	11871	880	2974	13220	980	14.2	9.6	M/R/O/J
3/4	19	0.031	0.79	2195	9757	650	2532	11258	750	2803	12458	830	2971	13209	880	3309	14710	980	12.5	8.4	M/R/O/J
3/4	19	0.035	0.89	2473	10992	650	2853	12683	750	3157	14035	830	3348	14881	880	3728	16572	980	11.1	7.5	M/R/O/J
1	25	0.031	0.79	2888	12838	650	3332	14813	750	3688	16393	830	3910	17380	880	4354	19355	980	9.5	6.4	M/R/J
1	25	0.035	0.89	3253	14463	650	3754	16688	750	4154	18468	830	4405	19580	880	4905	21805	980	8.5	5.7	M/R/J
1 1/4	31.75	0.028	0.71	3296	14653	650	3803	16907	750	4209	18710	830	4463	19837	880	4970	22092	980	8.5	5.7	M/R/J
1 1/4	31.75	0.031	0.79	3668	16304	650	4232	18812	750	4683	20818	830	4965	22073	880	5530	24581	980	7.4	5.0	M/R/J
1 1/4	31.75	0.035	0.89	4132	18367	650	4768	21193	750	5276	23454	830	5594	24867	880	6230	27692	980	6.7	4.5	M/R/J

				UltiMax(极元系列) HT						
Width		Thickness		Average Strength			Elongation	Length/Weight		Coil
in	mm	in	mm	lbs	N	N/mm ²	% (L=100mm)	ft/lb	m/kg	Winding
3/4	19	0.031	0.79	3444	15310	1020	≥ 10%	12.5	8.4	R/O/J
1 1/4	31.75	0.031	0.79	5755	25584	1020	≥ 10%	7.4	5	R/O/J

* M=Mini wound, R=Ribbon wound, O=Oscillated wound, J=Jumbo wound

Whatsapp:+8617826135709
Email:Sales@jhstrapping.com
www.jsjhpackaging.com

